


4CH PoE NVR

NVR2-4100P

1080P



Plug & View



MODEL	NVR2-4100P	
Video	Input	4CH RJ45 Direct Connection / Over Network
	Output	HDMI, VGA (800x600, 1024x768, 1280x1024)
	Decoding	H.264
Audio	Input	1CH + Depends on Camera Stream
	Output	1CH
	Two Way Audio	Yes
Bandwidth	Incoming	32Mbps
	Outgoing	24Mbps
Recording	Real-Time Recording	4CH 1080P Real-Time
	3MP	No
	2MP (1080P)	120FPS (NTSC)/100FPS (PAL)
	1.3MP (960P)	120FPS (NTSC)/100FPS (PAL)
	1MP (720P)	120FPS (NTSC)/100FPS (PAL)
	960H	No
	D1	120FPS (NTSC)/100FPS (PAL)
	CIF	No
	Recording Modes	Schedule, Manual, Motion, Sensor
Playback	Playback Channel	4CH
	Search Mode	Time, Event, File Management
Backup	USB	2 USB 2.0 Port
	DVD Burner	No
	Backup Format	AVI/DAT
Remote Application	Master Stream	Up to 4CH@Recording Resolution
	Sub-Stream	1-10/12FPS@720P, 1-25/30FPS@D1/CIF
	Browser	IE, Chrome, Safari, Firefox (Mac OS, Windows XP/Vista/7/8/10)
	CMS	Yes
	Mobile Application	Provision CAM for iPhone/Android Phone Provision HD for iPad/Android Tablet
	User Access	20 Users Online with Professional Authority Management
Alarm	Input	Depends on Camera
	Output	Depends on Camera
Storage	HDD	1 SATA (4TB)
	E-SATA	No
PTZ	Connection	Yes via Network
	Supported Controls	Pan, Tilt, Zoom, Preset, Cruise, Scan, Iris, Focus
	RS-485	No
Network	Ethernet	100 Mbps (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP, P2P
	ONVIF	Yes
PoE	Ports	Yes (4CH)
	Interface	10/100Mbps
	Standard	IEEE802.3AF
	Total Power	57W (Average 14.25W per Channel)
	Max. Power Consumption (Per Channel)	15W
Others	Power Supply	DC48V/1.5A
	Power Consumption (No HDD)	7W
	Dimension	W300xD260xH55mm
	Operation Temperature	0°C ~50°C