


IR FIXED LENS VANDAL-PROOF DOME CAMERA

DAI-340IP536+



- 1/3" CMOS Sensor
- 4 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR / BLC / HLC
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- Analytics Support
- 3.6mm Mega-Pixel Lens
- 15m IR Illumination
- PoE Support
- 1 Way Audio
- CVBS
- IP 66 Protection
- IK 10 Vandal Proof

Specifications

Camera	Video	Model	DAI-340IP536+
		Image Sensor	1/3" CMOS (16:9)
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
	Audio	Min. Illumination	Day: 0.045lux / Night: 0.01lux (@F1.8, AGC On) 0lux with IR on
		Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
		Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
		Noise Reduction	True WDR (120dB, HFR* Disabled) / BLC / HLC / ROI
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
Compression	Motion Detection	Yes	
	Analytics	Pro Level	
	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-Stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
Encode Mode	VBR/CBR		
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	15m (24 IR LED)
	Lens (Field of View)	3.6mm (71°)
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66 / Vandal Proof: IK10
	Bracket	3-Axis Gimbal
Connectivity	Dimensions	Φ116mm×91mm
	Weight(gross)	605g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (RCAX1)
	Mic Connectivity	1Ch Input
Network	SD Card	No
	RS485	No
	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS
Others	ONVIF	Yes
	Ethernet	100Mbps
Others	PoE	Yes
	Power Supply	DC12V/~440mA / PoE/~6.7W
	Work Environment	-30°C~50°C, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

