


40M IR MOTORIZED VF BULLET CAMERA

I4-340IP5MVF



- 1/3" CMOS Sensor
- 4 Mega-Pixel
- True Day & Night (IR Cut Removable)
- H.265 (HEVC) Compression
- 0 Lux (IR On) Min. Illumination
- ONVIF
- True WDR / BLC / HLC
- 3D Noise Reduction
- Motion Detection and Privacy Masking
- 3.3-12mm Motorized Lens with Auto-Focus
- 40m IR Illumination
- PoE Support
- Local Storage
- RS-485
- I/O – 1 Alarm in / 1 Alarm Out
- 2 Way Audio
- Technician Port
- IP 66 Protection

Specifications

Camera	Video	Model	I4-340IP5MVF
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	Two-way Audio
	Image Enhancement	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
Image Enhancement		Sharpness, Saturation, Brightness & Contrast Adjustable	
Noise Reduction		3D-DNR	
Image Orientation		Mirror/Flip	
Privacy Zone		Yes	
Motion Detection		Yes	
Compression	Video Compression	H.265 / H.264	
	Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240	
	Multi-stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)	
	Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264	
	Encode Mode	VBR/CBR	
Image Quality	Five levels under VBR; Free adjustment under CBR		

Housing	IR Distance	40m (48 IR LED)
	Lens	3.3-12mm Motorized with Auto-Focus
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis
	Dimensions	Φ109mm×284mm
Connectivity	Weight(gross)	1115g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS(BNCx1)
	Mic Connectivity	1Ch Input, 1Ch Output
	SD Card	Support Event Sub-stream recording over TF (64GB Max)
	RS485	Yes
Network	Alarm	1Ch Input, 1Ch Output
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~600mA / PoE/~8.5W
	Work Environment	-30 C~50 C, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

